

SAFETY DATA SHEET SETCRETE 2K PRO

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SETCRETE 2K PRO

Internal identification SET2KP/5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cementitious flooring product.

Uses advised against None

1.3. Details of the supplier of the safety data sheet

Supplier F.Ball and Co. Ltd.

Churnetside Business Park,

Station Road, Cheddleton,

Leek,

Staffordshire. ST13 7RS

Tel: 01538 361633 Mon-Fri 8.30am-5.00pm (Exc Bank Holidays)

E.mail: msds@f-ball.co.uk

1.4. Emergency telephone number

Emergency telephone 01538 361633 Mon-Fri 8.30am - 5.00pm (excluding Bank Holidays)

National emergency telephone UK - National Poisons Information Service Call 111

number Ireland - National Poisons Information Centre Call +353 1 809 2166

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Not Classified

Human health The product contains less than 2ppm soluble Chromium VI as a percentage of the cement

content. Persons with a known sensitivity to Chromium VI would be advised not to use this product. When mixed with water or gauging liquid splashes may cause serious eye damage.

Environmental The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic

organisms.

Physicochemical When handled correctly, undamaged units represent no danger.

2.2. Label elements

SETCRETE 2K PRO

Hazard pictograms



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/ attention.

P501 Dispose of contents/ container in accordance with national regulations.

Contains CEMENT

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

CEMENT 1-5%

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Remove affected person from source of contamination.

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get

medical attention if any discomfort continues.

Skin contact Remove contaminated clothing. Rinse immediately with plenty of water. Get medical attention

if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get

medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Irritation of nose, throat and airway.

Ingestion May cause discomfort if swallowed.

SETCRETE 2K PRO

Skin contact Prolonged skin contact may cause redness and irritation. May cause an allergic skin reaction.

Eye contact May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctorTreat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is non-combustible.

5.2. Special hazards arising from the substance or mixture

Specific hazards Dust may form explosive mixture with air. No unusual fire or explosion hazards noted.

Does not decompose when used and stored as recommended.

Hazardous combustion

products

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment

for firefighters

Wear chemical protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of dust. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning upAvoid generation and spreading of dust. Preferably remove spillage with a vacuum cleaner.

Collect spillage in containers, seal securely and dispose of as low hazard waste.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid handling which leads to dust formation. Good personal hygiene procedures should be

implemented. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container. Keep separate from food, feedstuffs, fertilisers and

other sensitive material. Store in a dry place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

SETCRETE 2K PRO

CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 total dust; 4 respirable dust mg/m³ Short-term exposure limit (15-minute): WEL Occupational Exposure Limit Value (8-hour reference period) 1 (R) mg/m³ WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment









Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of dust. Observe any occupational exposure limits for the product or ingredients.

Personal protection

Always check applicability with your supplier of protective equipment.

Eye/face protection

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Break through times can vary depending

on thickness, use and source. Change gloves regularly.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact. Wear apron or

protective clothing in case of contact.

Hygiene measures Provide eyewash station. Promptly remove any clothing that becomes wet or contaminated.

Wash promptly if skin becomes contaminated.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit. A half mask dust respirator approved to EN 149: 2001 FFP2 is

recommended. Ensure that the mask fits tightly to ensure an efficient seal.

Environmental exposure

controls

Residues and empty containers should be taken care of as hazardous waste according to

local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Dusty powder.

Colour Grey.
Odour Slight.

Odour threshold Not determined.

pH pH (concentrated solution): High alkaline pH when mixed with water.

Melting point Not determined.

Initial boiling point and range Not applicable.

Flash point Not applicable.

Evaporation rate Not applicable.

Evaporation factor Not applicable.

Flammability (solid, gas) Not determined.

Upper/lower flammability or

explosive limits

Not determined.

SETCRETE 2K PRO

Other flammability Not determined.

Vapour pressure Not applicable.

Vapour density Not applicable.

Relative density Variable, depends on packing effects and temperature

Bulk density Not determined.

Solubility(ies) Slightly soluble in water.

Partition coefficient Not applicable.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity Not determined.

Explosive properties Not determined.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Not applicable.

Comments Information given is applicable to the product in its ready-to-use form.

9.2. Other information

Other information None.

Refractive index

Particle size

Not determined.

Molecular weight

Not determined.

Volatility

Not applicable.

Critical temperature Not determined.

Volatile organic compound Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

Not determined.

10.2. Chemical stability

Saturation concentration

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

SETCRETE 2K PRO

10.6. Hazardous decomposition products

Hazardous decomposition

Does not decompose when used and stored as recommended.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Acute toxicity - oral

Notes (oral LD50) No specific test data are available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No specific test data are available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation No information available.

Animal data No specific test data are available.

Human skin model test No specific test data are available.

Extreme pH No specific test data are available.

Serious eye damage/irritation

Serious eye damage/irritation Irritation of eyes is assumed.

Respiratory sensitisation

Respiratory sensitisation No specific test data are available.

Skin sensitisation

Skin sensitisation No specific test data are available.

Germ cell mutagenicity

Genotoxicity - in vitroDoes not contain any substances known to be mutagenic.

Genotoxicity - in vivoDoes not contain any substances known to be mutagenic.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

IARC carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Reproductive toxicity -

development

Does not contain any substances known to be toxic to reproduction.

bots not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not relevant.

SETCRETE 2K PRO

General information No specific health hazards known.

Inhalation Dust in high concentrations may irritate the respiratory system. The product may contain a

small percentage of respirable crystalline silica. Prolonged exposure to dust may result in long

term irreversible effects

Ingestion Ingestion of small amounts is unlikely to cause a significant reaction. Larger doses may result

in irritation to the gastro intestinal tract.

Skin contact Prolonged or repeated contact with the powder or mixtures with water may cause burns

and/or irritant contact dematitis

Eye contact May cause irritation, soreness and reddening of the eyes

Acute and chronic health

hazards

No specific health hazards known.

Route of exposure Skin and/or eye contact

Target organs Eyes Skin

Medical symptoms Irritation of eyes and mucous membranes. Allergic rash.

Medical considerations Pre-existing eye problems. Skin disorders and allergies.

SECTION 12: Ecological information

Ecotoxicity The product may affect the acidity (pH) of water which may have hazardous effects on aquatic

organisms.

12.1. Toxicity

Toxicity Not available

Acute aquatic toxicity

Acute toxicity - fish Not determined

Acute toxicity - aquatic

invertebrates

Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity -

microorganisms

Not determined.

Acute toxicity - terrestrial Not determined.

Chronic aquatic toxicity

Chronic toxicity - fish early life Not determined.

stage

Short term toxicity - embryo

and sac fry stages

Not determined.

Chronic toxicity - aquatic

Not determined.

invertebrates

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Phototransformation Not determined.

Stability (hydrolysis) Not determined.

SETCRETE 2K PRO

Biodegradation Not determined.

Biological oxygen demand No specific test data are available.

Chemical oxygen demand No specific test data are available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not applicable.

12.4. Mobility in soil

Mobility The product is non-volatile.

Adsorption/desorption

coefficient

Not determined.

Henry's law constant Not determined.

Surface tension Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Small quantities may be mixed with water, allowed to cure fully and disposed of as low hazard

waste. Larger quantities should be disposed of as hazardous waste via a licensed waste

operator.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

SETCRETE 2K PRO

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

Guidance Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Health and environmental

listings

None of the ingredients are listed.

Authorisations (Annex XIV Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Annex XVII Regulation 1907/2006)

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Technical Data Sheet

Key literature references and

sources for data

Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure

Limits.

Revision comments SDS Updated

Revision date 24/03/2020

Revision 5

Supersedes date 31/08/2018
SDS status Approved.

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.