

ACRYLIC PRIMER

READY TO USE • EASY TO USE • FAST DRYING



TRADE QUALITY YOU CAN TRUST

SETCRETE™ ACRYLIC PRIMER

A low VOC emulsion primer designed to promote the adhesion of SETCRETE™ FLOOR LEVELLING COMPOUNDS to smooth absorbent and non-absorbent surfaces.



DRYING TIME

- GENERAL PURPOSE PRIMER FOR BOTH ABSORBENT AND NON-ABSORBENT SURFACES
- PROMOTES GOOD ADHESION FOR LEVELLING COMPOUNDS
- COLOURED TO PROVIDE COVERAGE CONTROL

SETCRETE™ ACRYLIC PRIMER prevents unacceptably rapid drying of SETCRETE™ FLOOR LEVELLING COMPOUNDS over absorbent subfloors, and promotes adhesion to non-absorbent surfaces. It is suitable for use over normal underfloor heating installations and is coloured green to provide the user with visual control of coverage uniformity.

SETCRETE™ ACRYLIC PRIMER should be used on absorbent surfaces such as concrete, sand/cement screeds, plywood and hardboard. It should also be used on non-absorbent surfaces of terrazzo, power floated concrete, quarry and ceramic tiles, sound asphalt, well bonded epoxy and polyurethane coatings and minimal existing adhesive residue.

The product complies with the standards set by GEV EMICODE.

Preparation

Floor surfaces must be suitably prepared: sound, smooth, dry – less than 75% Relative Humidity (less than 65% Relative Humidity for wood floor installations) and free from contaminants that may prevent adhesion. Concrete and sand/cement screeds must be fully cured and any laitance or surface treatments must be removed prior to the application of SETCRETE™ FLOOR LEVELLING COMPOUNDS. The temperature of the subfloor must be above 10°C when the primer is applied and underfloor heating must be off for at least 48 hours before, during and after application. Ensure the subfloor incorporates an effective damp proof membrane.

Mixing

SHAKE WELL BEFORE USE

For absorbent surfaces add 1 part primer to 4 parts of water and stir until thoroughly dispersed. For non-absorbent surfaces, apply the primer undiluted. Apply evenly to the whole surface to be treated and allow it to dry completely. For external concrete and sand/cement screeds, prime SETCRETE™ ACRYLIC PRIMER diluted 1:7 with water prior to the application of SETCRETE™ EXTERIOR FLOOR LEVELLING COMPOUND.

Tools

Paint roller. Wash tools with warm water immediately after use.

Coverage

Applied dilute to absorbent : 50m².

Applied undiluted to non-absorbent : 25m².

Rates will vary based on the condition of the subfloor.



Drying Time

This will vary depending on temperature, humidity and absorbency of the subfloor.

From 20–30 minutes at 20°C on absorbent subfloors.

From 60 minutes at 20°C on non-absorbent subfloors.

These times will be extended at lower temperatures.

Storage and Shelf Life

Store in unopened containers under good conditions. Store between 5°C and 30°C. Protect from frost. Use within 24 months.

Health and Safety Advice

This product is not classified. Obtain the relevant Safety Data Sheet and follow the advice given. These can be found at www.setcrete.co.uk alternatively these can be obtained from the point of purchase or from F. Ball and Co. Ltd. at the address below.

For further information or technical assistance about SETCRETE™ products and to confirm this data sheet is current, please contact Technical Service Department

Packaging

2.5 litre bottle.



For further information or technical assistance about SETCRETE™ products and to confirm this data sheet is current, please contact Technical Service Department.

4810 08/24

F. Ball and Co. Ltd.

Churnetside Business Park, Station Road, Cheddleton, Leek, Staffordshire. ST13 7RS, United Kingdom.

Tel: +44 (0) 1538 361633, Email: contact@setcrete.co.uk

www.setcrete.co.uk